

NIPPON KAIJI KYOKAI

Certificate

Certificate No. TA21730E(R)

OF

APPROVAL

Item

: Shipboard Incinerator

Product name

: OSG-1500SDA

Manufacturer

: Sunflame Co., Ltd.

1-30, Nishinohata, Okubo-cho, Uji-city,

Kyoto, Japan

Max. capacity

: 1500kW

: 200 kg/h of specified waste

: 161 kg/h per burner

O2 Average

in combustion chamber/zone

: 8.3 %

CO Average in flue gas

: 75 mg/MJ

Soot number average

: 3.0 Bacharach scale

Combustion chamber flue gas

outlet temperature average

: 1039 ℃

Amount of unburned

components in ashes

: 2.5 % by weight

Documentation

: Incinerator. W.No.5805-NA Ceramic Refractory: ICW-16000.

THIS IS TO CERTIFY that the prototype of the above shipboard incinerator has been examined and tested in accordance with the requirement of the *Standard Specification for Shipboard Incinerators* set out at Annex to the Resolution MEPC.244(66) and the prototype of the above shipboard incinerator has been approved by Nippon Kaiji Kyokai with approval No.08CD33S.

A copy of this certificate should be carried on board a vessel where this type of incinerator is fitted.

This certificate is valid from 10 May 2021 until 9 May 2026. Issued at Tokyo on 24 June 2021.

NIPPON KAIJI KYOKAI

Y. Takao General Manager

Material and Equipment Department